Technical Data Sheet



KYNOS PARSOL Spindle Oil

KYNOS LUBRICATION PRIVATE LIMITED

info@kynosoils.com / sales@kynosoils.com

PARSOL: Refined Mineral Spindle Oil for High-Speed Machine.

PARSOL is a light refined mineral oil intended to lubricate high speed machine elements operating under medium load and temperature conditions.

It is ashless and contains rust and corrosion inhibitors providing excellent oxidation resistance and thermal stability at elevated temperatures

PARSOL fluids are particularly recommended to lubricate spindles, conveyor bearings, rolling bearings and automatic clutches bearings. PARSOL can be applied by dipping, dripping, spraying or centralized systems. It meets ISO-L-FC under the standard ISO 6743/2.

Benefits

- Zinc Free (Ashless Technology)
- Excellent protection against Rust and Corrosion.
- Reducing Wear.
- Increased Heat and machine management.
- Longer Spindle bearing life.
- Increased productivity.

Typical Performance Data

Properties	Test Method	PARSOL 2	PARSOL 4	PARSOL 10
Viscosity, cSt @ 40 °C	ISO 3104	2.2	4.6	10
Colour	ASTM D-1500	Yellow	Yellow	Yellow
Appearance	Visual	Oily Liquid	Oily Liquid	Oily Liquid
Flash Point, °C	ISO 2592	>100	>120	140
Pour Point, °C	ISO 3016	-20	-15	-14
ISO Grade	ISO 3448	2	5	10

^{*}All performance data on this Technical Data Sheet are indicative only and may vary during production.